

FEATURES:

- Meets with TIA/EIA-568-C.3 and ISO/IEC 11801 specifications for insertion loss and return loss
- Environmentally stable in optical performance
- Provide total immunity to electrical interference
- RoHS compliant



APPLICATIONS:

- Telecom network
- CATV
- FTTH
- End equipment
- Local Area Network
- Test equipment

TYPICAL PERFORMANCE:

Connector Type		ST	LC	SC	FC
Insertion Loss		≤0.3dB	≤0.3dB	≤0.3dB	≤0.3dB
Return Loss	UPC	≥50dB	≥50dB	≥50dB	≥50dB
	APC	≥60dB	≥60dB	≥60dB	≥60dB
Interchange capability (1000 times)		<0.1dB	<0.1dB	<0.1dB	<0.1dB
Impact 1.5mm drop, 8 times		<0.1dB	<0.1dB	<0.1dB	<0.1dB
Working temperature		-20℃~60℃	-20℃~60℃	-20℃~60℃	-20℃~60℃

Part No. 22vwxyzzz**Ver. 1802****Product Specification****ORDERING INFORMATION:**

Part NO	22vwxyzzz
Description:	Premium Line fiber optical pigtail, SM 9/125um, simplex
v, mode	3: G652D 6: G657A2
w, O.D.& Sheath	1: 0.9mm PVC 3: 0.9mm LSOH
x, connector type	1: SC 2: ST 3: FC 4: LC
y, mode	3: UPC 5: APC
zzz, length	010: 1M 015: 1.5M 020: 2M 030: 3M

Other length is available upon the request.

Premium-Line Systems GmbH. Rosenheimer Str.89 D-83064 Raubling. Germany

► TEL:+49(0)8035 9836 0 ► FAX:+49(0)8035 9836 22

Premium Line Systems GmbH reserves the right to change specifications without prior notice.